

# SLIMLINE FLOOD RANGE

## LED Floodlights



### 50W Floodlight

#### PLFL50W

50W, 7500lm,  
247x255x57mm

### 100W Floodlight

#### PLFL100W

100W, 15000lm,  
301x284x64mm

### 150W Floodlight

#### PLFL150W

150W, 22500lm,  
343x318x65mm

### 200W Floodlight

#### PLFL200W

200W, 30000lm,  
398x368x69mm

### PRODUCT FEATURES


- 5 Year replacement warranty
- Aluminium construction with tempered glass - exceptional impact resistance
- Shadow free security and spot lighting for indoor/outdoor use
- High lumen output 150lm/W
- 120° Beam angle
- IP66 Rated / IK08 rating



5700K



IP Rating



Warranty



Lifespan

### TECHNICAL SPECIFICATIONS

LIFESPAN	76,000 hours
INPUT VOLTAGE	AC220-240V
BEAM ANGLE	120°
OPERATING TEMP	-30°~+40°C
CERTIFICATIONS	RoHS, SAA, CE
IP RATING	IP66
FREQUENCY	50Hz

CRI	>70
POWER FACTOR	>0.90
LED TYPE	SMD 2835
COLOUR OPTIONS	Black
DIMMABLE	No
COLOUR TEMP	6700K